



# EQUIPMENT

### **REQUEST FOR QUOTE**

6275 Heisley Road Mentor, Ohio 44060 Phone: 1-800-899-2680 or 440-358-7060 Fax: 440-358-7061

Return completed form by fax to: Polychem Equipment Group at 440-358-7061 or e-mail to mcojocaru@polychem.com

AUTHORIZED DISTRIBUTOR INFORMATION		END USER INFOR	MATION			
Distributor			0			
Address.			Address			
Phone:			Phone:			
			L-Indii			
Address Quote To: Se	end Quote By:	Type of Quote Required:	Date Submitted:			
End User	E-mail	Budgetary	Date Needed:			
Distributor	Fax	Firm				
L	Regular Mail					
Describe existing strapping	oquinmont (if onv):					
Describe existing strapping	equipment (il any).					
PRODUCT INFORMAT	ION					
Describe product to be stra	ipp <u>ed:</u>					
Breduct Dimensioner	Usiaht	14/: -141-	Longth	)M/aimht		
Product Dimensions:	Height	Width	Length	Weight		
(including pallet)		(90 degrees to flow)	(parallel to flow)			
Minimum						
Maximum						
Other						
PALLET INFORMATIO	N					
Is the product on a pallet?		Yes	No			
If yes, what is bottom board orientation relative to the conveyor?						
Perpendicular	)0000000000	$\sum$	Parallel			
			Bottom board width?			





# EQUIPMENT

## **REQUEST FOR QUOTE**

6275 Heisley Road Mentor, Ohio 44060 Phone: 1-800-899-2680 or 440-358-7060 Fax: 440-358-7061

Return completed form by fax to: Polychem Equipment Group at 440-358-7061 or e-mail to mcojocaru@polychem.com

#### Specify Pallet Type:

Two-way			Single wing (shown) Double wing	
Four-way (GMA)			Postal	6100
Plastic 4 -way Solid Deck & Base			Dimensions L = A = B =	
Other (please sket	ch)		W = C = D =	
If strapping though palle	et void, specify void opening he	əight:	h =	
Is existing conveyor equ				
Yes If yes, specify type:		Powered	Non-powered (gravit	ty)
Is conveyor equipment l	being supplied by Polychem?	Powered	Non-powered (gravit	ty)
If yes, specify type:				
Conveyor Dimensions:	Height (Top of Rollers):		Roller Diameter:	
	Useable width:		Roller Spacing:	
	Overall Width:		Other:	





## EQUIPMENT

### **REQUEST FOR QUOTE**

6275 Heisley Road Mentor, Ohio 44060 Phone: 1-800-899-2680 or 440-358-7060 Fax: 440-358-7061

Return completed form by fax to: Polychem Equipment Group at 440-358-7061 or e-mail to mcojocaru@polychem.com

#### INSTALLATION INFORMATION

Ceiling Height:		Product Temper	ature:						
Access Door Opening:		Operating Temperature:							
Electric Power Available:	440 Volt - 3 Phase 220 Volt - 3 Phase	Specify any limitations to standard installation:							
STRAPPING INFORMATION									
Strap Type:	Polyester Polypropylene		:						
		Break Strength	:						
Strap Pattern:	1 X 0 2 X 0	1 X 1 2 X 2	Other (please specify)	x x					
If strap placement is critical, specify strap location on load/pallet:									
Production Throughpu	t:								
Average Loads per Hour:			Production Hours per Day:						
Peak Load per Hour:			Production Days per Week:						
Options:									
Semi-automatic (Strapping cycle initiated by operator)			Compression	Force =					
Automatic (Strapping cycle initiated automatically)			Top corner protector						
Fixed bottom track (For strapping around entire package)			Bottom corner protector						
Pallet void feeder (For strapping through pallet void)			Top dunnage/bunk						
Over/Under (For str	apping both around pack	age and through pallet void)	Bottom dunnage/bunk						
Fixed head (Requir	Fixed head (Requires product to be positioned nest to strapping head)								
Indexing head (Head indexes out to meet package. Positioning not a critical)									