

STRAPPING

0875

MOD.







White goods



## 0875-AB

The 0875AB automatic lateral strapping machine was designed to apply vertical straps to palletized products. It comes with a strapping head that works either with polypropylene or polyester straps. It can be placed in full automatic packaging lines, where, by signals exchange can communicate with other machines. It can also operate in stand alone mode. It may also feature a touch-screen operator panel through which to manage all machine functions.

## **Technical data**

Air supply Pressure


Consumption


Power supply	
Voltage	400 V (50Hz)
Installed power	~ 2 kW

5,5 ÷ 6,5 bar


~ 5 NL/cycle

## **Standard machine dimensions**





L: 4130 mm





Coil size	
Max internal diameter	390 ÷ 405 mm
Max external diameter	600 mm

Pack size (standard machine)	
Lenght	1200 mm
Width	800 / 1200 mm

## Applicable strapping heads

TR1400 / TR1400HD / TR1800 / SONIC Plus / TR200

Strap Type of strap

Polyester (PET) Polypropylene (PP)



Packaging line with 0875 & TR200 and conveyors



Officina Meccanica Sestese S.p.A. 9 Via Borgomanero, 44 - 28040 Paruzzaro (NO) 📞 Tel.+39 0322 541411 🖶 Fax +39 0322 53157

Sword-bayonet to strap through pallet void

www.omsspa.com info@omsspa.com

