CB7000SQ




SQUARING CORRUGATED BUNDLER AUTOMATIC STRAPPING MACHINE



- All Electric Press, No Pneumatic
- Direct Drive Strapping Head with German Brushless DC
- Free Access to Strap Guides
- Single, Double, Continuous Strapping or Transit Mode
- Full Automatic with Variable Speed Conveyor



Free Access to Strap Guide



Siemens PLC Control

Specifications	
Arch Sizes	65"(W) X 17"(H)
Cycle Rate	Up to 24 bundles/minute (single strap)
Strap Width	5mm, 6mm, 9mm PP Strap
Strap Tension	2 to 70 lbs
Transport Speed	49 to 196 ft/minute
Electrical Requirements	220V, 380V, 400V, 415V 50/60Hz 3 Phase

Options

Dual dispensers with auto coil change

Uplift Support for heights greater than 39"

3-Sided Squaring Corrugated Bundler



CB7000SQ

Auto Strap Feeding

- Full Color Touch Screen
- Robust & Compact Mechanical Strapping Head CB7000SQ uses the latest DC brushless motor technology to provide the highest level of accuracy and reliability in the market. All motors are German-made
- Siemens PLC Control Provide easy adjustments, TEACH-IN programming, and troubleshooting guides.
- Free Access to Strap Guides Unblocking the guides enables free and quick access to the strap guides without use of any tool.
- 3 -Side Squaring Bundle Control

The electric-driven side squaring and backstop devices optimize the integrity of bundles for strapping. Unique front and rear squaring mechanism with independent control system improves squaring performance over a wider range of bundle sizes.

Automatic Bundle Size Setup System

The automatic setting mode makes CB7000SQ fast setup for bundle size change in 15 seconds. It minimizes costly downtime.

Motorized Full-width Press Bar

Motorized full-width press bar provides the highest reliability and stability of the movement. It also offers easy adjustments for different press bar position to increase str<u>apping speed</u>.

Hinged Roller Table

Easy and effort less to open the table top for cleaning and maintenance. Ergonomic design

Good for Small Bundle

The round belts on rollers nearby strapping head helps move small bundles across strapping position smoothly. It allows for a minimum bundle size of width 8'' (W) x10'' (L).

6277 HEISLEY ROAD MENTOR, OHIO 44060 (440) 357-1500 FAX (440) 352-9553

WEST COAST DISTRIBUTION CENTER 11920 ALTAMAR PLACE SANTA FE SPRINGS, CA 90670 (562) 903-4576 FAX (562) 903-4579 1-800-899-0822



CALL TOLL FREE 1-800-548-9557 www.polychem.com